

## 4' Vapor TightLED - Wet Location

This is a 4' fixture that has a gasket and enclosed protecting the LED's from the elements of water, dust, and impact. This fixture comes with a clear lens allowing for maximum light pass-through. Utilizing LED technology that delivers 93% of the initial light even after 100,000 hours of use, providing a lighting solution second to none in the industry.



Pictured: 4' 4 Module Water Tight Fixture

### System Configurations:

| Fixture Config. | Wattage | Lumens | Efficacy |
|-----------------|---------|--------|----------|
| 4' 2 Module     | 52      | 6,689  | 131.75   |
| 4' 4 Module     | 48      | 7,105  | 147.73   |
| 4' 4 Module 4A  | 98      | 13,239 | 134.11   |

### Notes:

|   |
|---|
| Performance data taken at Tc = 45°C ambient.  |
| Life expectancy = > 100,000 hours   |
| Lumen maintenance value is based on LM80 testing and TM-21 calculation projections. |
| CRI = > 82  |
| Warranty : Limited 7 years  |



### Regulatory

|                                      |
|--------------------------------------|
| Recognized - UL8750 CAN/             |
| CSA-C22.2 No. 250.13-12 / ETL Listed |
| RoHS Compliant                       |

| Part Number         | GLWT        | 4      | 2                  | MV                                 | 50                                     |
|---------------------|-------------|--------|--------------------|------------------------------------|--|
| Example Part Number | Part Number | Length | # LED Modules      | Voltage                            | Color Temperature                      |
| Ordering Options    | GLWT        | 4'     | 2=2<br>4=4<br>4=4A | MV=<br>120/277v<br>HV=<br>347/480v | 30 - 3000k<br>40 - 4000k<br>50 - 5000k |